

Reducing urban glow Bundaberg

Turtle friendly lighting guide for residential properties



How to play your part as a resident

Tips

- Use LEDs and compact fluorescents with lower temperatures and warmer colors.
 Lights with lower color temperatures (2700–3000 K) are called "warm colors" (yellowish), while color temperatures over 5000 K are called "cool colors" (bluish).
- Use dimmers, motion sensors, or timers on outdoor lighting.
- Use outdoor lighting fixtures that shield the light source to minimize glare and light trespass.
- Turn off unnecessary indoor lighting, particularly in empty buildings at night.
- Maintain as much overnight dark as possible.
- If you live in a high-rise building, use drapes or blackout curtains to reduce light emissions, particularly during turtle nesting and hatching seasons.


Balcony or deck lighting




Poorly directed balcony or deck lighting can cause problems on sea turtle nesting beaches.



Better Completely shielding fixtures with a sheet of metal flashing can reduce stray light reaching the beach.




Best Louvered step lighting is one of the best ways to light a balcony or deck that is visible from nesting beaches.



Diagrams of common lighting fixtures showing mounting position, light distribution and overall suitability for use near turtle nesting beaches.

For purposes of recommending suitable mounting distances from nesting beaches, the crest of the primary dune is considered to be the landward limit of the beach. Fixtures are assessed for their suitability in minimising direct and indirect lighting of the beach. For all fixtures, glowing portions or luminaries (including reflectors and globes) should not be visible from the turtle nesting beach.



Wall mounted area lighting

Mounting suitability


Poor. Very poor when mounted on upper stories.

Directional suitability

Poor.

Overall suitability

Poor, not suitable for the beach sides of buildings.



Wall mounted area lighting

Mounting suitability


Poor. Very poor when mounted on upper stories.

Directional suitability

Poor.

Overall suitability

Poor, not suitable for the beach sides of buildings.



Decorative cube light

Mounting suitability

Fair if mounted at heights lower then 1.8 metres.


Poor if mounted higher.

Directional suitability

Very poor.

Overall suitability

Very poor. This fixture is difficult to shield and should not be used near turtle nesting beaches.



Decorative globe light

Mounting suitability


Fair if mounted at heights lower than 1.8 metres, poor if mounted higher.

Directional suitability

Very poor.

Overall suitability

Very poor. This fixture is difficult to shield and should not be used near turtle nesting beaches.



Lighting bollards with hidden lamp

Mounting suitability


Good if mounting height is near 1 metre.

Directional suitability

Poor to fair.

Overall suitability

Fair, good if additional shields on the beach side of the fixture are used.



Low height (short) tier lighting

Mounting suitability


Good if mounted at foot level.

Directional suitability

Poor but can be good if the fixture has louvres that eliminate lateral light.

Overall suitability

Fair, good to excellent if used so that vegetation and topography block it's light from the beach.



Lighting bollard with louvres

Mounting suitability


Good if mounted at foot level.

Directional suitability

Poor but can be good if the fixture has louvres that eliminate lateral light.

Overall suitability

Fair, good to excellent if used so that vegetation and topography block it's light from the beach.



Ground mounted floodlighting

Mounting suitability


Poor because of its upward aim.

Directional suitability

Fair to good.

Overall suitability

Fair to poor if directed away from the beach, very poor if directed toward the beach.



Decorative carriage lighting

Mounting suitability


Fair if mounted at heights lower than 1.8 metres, poor if mounted higher.

Directional suitability

Very poor, Fair if shielded properly.

Overall suitability

Poor.



Ceiling mounted area lighting: fixtures with refracting gloves or convex lenses

Mounting suitability


Poor if mounted on the beach side of buildings or on upper stories. Good if shielded from the beach by buildings.

Directional suitability

Poor.

Overall suitability

Poor to fair, depending on mounting location.



Ceiling recessed down lighting: fixtures with baffles to eliminate lateral light

Mounting suitability


Good to excellent when mounted in lower story ceilings and soffits.

Directional suitability

Excellent.

Overall suitability

Good to excellent.



Wall mounted area lighting: 'jelly jar' deck light fixture

Mounting suitability


Poor. Very poor when mounted on upper stories.

Directional suitability

Poor.

Overall suitability

Poor.



Louvred step lighting


Mounting suitabilityExcellent if mounted at foot level.

Directional suitability

Excellent.

Overall suitability

Excellent.



Wall mounted down lighting

Mounting suitability

Good to excellent when mounted on lower story walls.

Directional suitability

Excellent.

Overall suitability

Good to excellent.

This page is intentionally blank 6

